

# L.S.A. MANUAL

---



**PETTA GP**

## GRUPPI DISERBANTI PORTATI A BASSA PRESSIONE

### Caratteristiche tecniche

- cisterna in polietilene a svuotamento totale
- cisterna lavamani
- livello esterno
- cisterna lavacircuito
- telaio profilato pesante in acciaio zincato a caldo con attacchi a forcella
- pompa a membrana a bassa pressione
- comando proporzionale manuale a 5 sezioni con filtro con rubinetti separati per agitatore e miscelatore**
- filtro di aspirazione esterno con valvola di autorimpimento
- agitatore idraulico ispezionabile
- barra idraulica chiusura a croce a 2 pistoni con bilanciere con bloccaggio meccanico manuale
- snodo e molle antiurto
- uniget antigoccia con ugelli in kematal blu e filtrini antigoccia
- tubi oleodinamici con innesti rapidi sul trattore
- senza giunto cardanico

## LOW PRESSURE MOUNTED WEED SPRAYERS

### Technical features

- fully emptying polyethylene tank*
- circuit-washing tank*
- hand-washing tank*
- external level*
- hot galvanized steel heavy set-in bar frame with fork attachment*
- low pressure diaphragm pump*
- 5 section proportional manual control with filter with separated taps for agitator and mixer*
- external suction filter with self-filling valve*
- dismountable hydraulic agitator*
- 2 piston hydraulic cross bar with rocker arm with manual mechanical blocking*
- joint and shockproof rings*
- antidrip single-jet with blue kematal nozzles and anti-drip nozzles*
- oil pressure hoses with quick release couplings on the tractor*
- without cardan shaft*

Modello <i>Model</i>	Capacità <i>Capacity</i> Lt.	Larghezza <i>Width</i> mm.	Profondità <i>Depth</i> mm.	Altezza <i>Height</i> mm.	Potenza trattrice <i>Tractor power</i> HP.
Lsa	600	1350	965	1250	60/70
Lsa	800	1780	900	1500	80/100
Lsa	1000	1780	900	1700	80/100